

2600 Spray-Grip Adhesive for Vinyl Tile

Installation

DESCRIPTION

2600 Spray-Grip Adhesive for Vinyl Tile is a no VOC, non-flammable water based adhesive formulated for use with Roppe Vinyl and LVT Tiles. The immediate high sheer strength allows for foot traffic after installation and eliminates the worry of adhesive displacement due to early traffic. 2600 Spray-Grip Adhesive for Vinyl Tile reduces the amount of adhesive on projects by up to 80%, therefore reducing the amount of weight during shipment and manufacturing. 2600 Spray-Grip Adhesive for Vinyl Tile canisters are completely recyclable and the design allows for the complete use of the contents, so there is no waste.

COLOR

White

PACKAGING

22 ounce Aluminum Can, 6 Cans per Case, 12 Lbs per Case

TROWEL SIZE

No Trowel Needed

COVERAGE

Approximately 150-185 Square Feet per Can

Coverages shown are for estimating purposes only, actual job-site coverages may vary according to substrate conditions, trowel conditions and/or application methods.

APPROVED SUBSTRATES

Properly prepared interior porous and non-porous on grade, below grade and above grade Concrete, Terrazzo, Ceramic Tile, Metal, well adhered Epoxy, Wood and Cement-based self-leveling underlayments and patching compounds.

ADHESIVE WORKING TEMPERATURES

Area and material should be maintained between 65°F (19°C) and 85°F(30°C) for at least 48 hours before installation, during installation, and thereafter.

ADHESIVE WORKING TIME

Flash Time*: 15-20 Minutes, Allow material to dry until there is no transfer to the finger when touched

Working Time**: 120 Minutes, Protect from contamination from dust

Flash and Working Times will vary based on job-site conditions, trowel size and application procedures.

MIXING PROCEDURES

Shake each can thoroughly for 1 minute before use.

MOISTURE AND PH REQUIREMENTS

ASTM F 1869; Calcium Chloride, 8 lbs
ASTM F 2170; Relative Humidity, 90%
pH; 11 or less

APPROVED PRODUCTS FOR USE

Northern Timbers, Northern Leathers, SafeTcork Solid Vinyl Tile



ADHESIVE REPLACED

ROP400 Spray Adhesive for Vinyl Tile

CLEAN UP

Remove any adhesive from surface of materials with a soft clean cloth with warm soapy water, while the adhesive is still wet. If adhesive has dried, gently clean the surface with a soft clean cloth with denatured alcohol or mineral spirits and then rinse well with warm soapy water and clean cloth to prevent discoloration.

VOC INFORMATION

Compliant, per SCAQMD Rule #1168
0 Grams / Liter of Coating (calculated)

LIMITATIONS

All Traffic, Immediately

Heat Welding, 3 Hours after Installation

Maintenance, 48 Hours after Installation

Not for use outdoors

Not for use over existing floor covering or old adhesives

SHELF LIFE

Shelf life is one year when stored between 65° F (18° C) and 90° F (32° C) in original unopened container

DATE CODE DESCRIPTION

121212-2 - Printed on Bottom of Container

12, Production Month

12, Production Date

12, Production Year - Last Two Digits

-2, Production Line

FREEZE THAW STABILITY

Material is not Freeze Thaw Stable, Protect material from freezing

QUALIFICATIONS

FloorScore, CHPS

As not all information can be covered within this general guide, please refer to the appropriate Product Data Sheets, Installation and/or Maintenance Instructions for additional detailed information. Obtain from www.roppe.com by clicking the Technical Support link or by contacting Roppe Customer Service.

*Flash time is the waiting time required prior to installing the Tile.

**Working time is the time for the adhesive to accept the Tile.