

Environmentally friendly, made from post consumer bias-ply tires. Attractive carpet-like surface provides a touch of luxury in areas of frequent foot traffic. Traps dirt, absorbs moisture, and protects floors. Easily maintained with vacuum cleaner or hose. Suitable for any entrance or as wall to wall floor covering. Meets Federal flammability regulations DOC FF 1-70. According to AMCIC Test, Dura-Tile exceeds the minimum char radius of 3" Average car, per 8 strips tested, .75" radius.

Material: Rubberized fabric strips with chenillelike surface cut from recycled tires bonded to nonflammable base.

Thickness: 3/8" (with $+1/8 \sim 0$ ")

Nosing (optional:) Black beveled vinyl nosing for finished approaches on surface installation.



Earthtone



Tone



Green

Tone



Tone



Charcoal

Tone

Tone



Ordering Information

Dura-Tile & Dura-Tile RollsTM

Item No.	Size	Weight
345S1212	12" x 12"	2.3 lbs./sq.ft.
345R1230	12" x 30'	69 lbs./roll

Colored Dura-TileTM

Item No.	Size	Weight
345S1212*	12" x 12"	2.3 lbs./sq.ft.
*Use Color Codes:	Red(RD), Blue	(BL), Green(GN),
Brown(BN), Charc	coal(CH)	

Adhesive & Nosing

Item No.	Description	Weight
345ADHSV	1 gallon can adhesive	9 lbs. ea.
345NOSE	Beveled Nosing	0.5 lbs./lin.ft.

Dura-Tile II 95% Recycled Content

Size	Rubber/Tile	Tires/Tile	1 Tire
12" x 12"	2 lbs.	.07	15 Tiles

1 Tire = 30 lbs.



1-800-810-7847 www.commercialmatsandrubber.com