THE ORIGINAL FLEXIBLE SURFACE APPLIED MAT

NOW MESH REINFORCED FOR ADDED STRENGTH & INCREASED DURABILITY

Developed in 1994, the original RediMat, now mesh reinforced, is constructed of an extremely durable, UV protected, flexible polyurethane. It has a proprietary pre-applied adhesive system that enables installation in less than 5 minutes. The flexible RediMat can be used on a variety of surfaces with no drilling required for traditional projects - drastically reducing labor time and expense, but not at the cost of durability.







- Installs on asphalt or concrete multi surface adhesive system
- No adhesives or anchors required exclusive peel & stick technology
- Unbreakable will not chip, crack or splinter
- Conforms to uneven surfaces flexible mesh-reinforced polyurethane material
- Parking Structure approved installs with no anchors for raised floor applications
- · Also available as direction bar or guidance mats

Asphalt Install

USES - ANCHORS / NO ANCHORS:

- Without Anchors traditional installations such as sidewalks, commercial properties, parking structures, commercial properties
- With Anchors when specifically required via local / project specifications or for challenged surfaces

INSTALLATION:

Easiest installation of any surface applied mat. Just peel and stick, roll to insure a secure bond and apply an edge sealer bead around the perimeter. Optional installation anchors provided for challenged surfaces or local requirements.

PHYSICAL CHARACTERISTICS:

- Hardness 90 (Shore A)
- Stain Resistance No Significant Change
- **Dome Spacing -** Inline, 2.35", 2.4" (CA 3x4)
- Slip Resistance .90 per ASTM C1028
- Taber Abrasion (1000gms/1000 cycles) 150mgs
- Color Integral Throughout



Brick Red







ASK ABOUT OUR DIRECTIONAL BAR MATS

Safety Yellow FED 33538

FED 20109



FED 17038



3' x 2.5'

3' x 4'

3' x 2.5'

3' x 2.5 3' x 5'

Wedge 10 ft radius