

700 Series Wall Base

MADE IN THE USA

PRODUCT QUICK SPEC



ROPPE.

Proven. Flooring. Experiences.

1. MANUFACTURER

Roppe Corporation

1602 N. Union Street

P.O. Box 1158

Fostoria, Ohio USA 44830-1158

t: (419) 435.8546 | tf: (800) 537.9527

f: (419) 435.1056

E-mail: sales@roppe.com | Internet: www.roppe.com

2. PRODUCT DESCRIPTION

Roppe 700 Series Wall Base is designed for use in both commercial and residential wall base applications. Easier to work with and providing more flexibility than vinyl base products, Roppe's unique blend of thermoplastic rubber and vinyl makes the 700 Series an attractive and economical choice for a variety of applications.

Available Styles (All Dimensions Nominal)



Profile: Standard Cove

Gauge: 1/8" (3.2 mm)

Heights: 2 1/2" (63.5 mm), 4" (101.6 mm) or 6" (152.4 mm)

Lengths: 48" (1.22 m) Pieces & 120' (36.58 m) Coils

Factory Corners: Inside & Outside Corners in 2 1/2" (63.5 mm), 4" (101.6 mm), 6" (152.4 mm) heights with 3" (76.2 mm) returns



Profile: Standard No Toe

Gauge: 1/8" (3.2 mm)

Heights: 2 1/2" (63.5 mm), 4" (101.6 mm) or 6" (152.4 mm)

Lengths: 48" (1.22 m) Pieces & 120' (36.58 m) Coils

Factory Corners: Outside Corners in 2 1/2" (63.5 mm) or 4" (101.6 mm) heights with 3" (76.2 mm) returns

3. TECHNICAL DATA

ASTM F 1861 - Type TP, Group 2, Styles A & B

ASTM E 648, Critical Radiant Flux - Class 1 >.45 W/cm²

ASTM E 662, Smoke Density - Passes <450

ASTM E 84, Surface Burning - Class B

According to the BOCA (Building Officials & Code Administrators International Inc.) codes and the NFPA (National Fire Protection Agency), Accessories are considered incidental trim. According to these sections, any incidental trim not in excess of 10% of the aggregate wall and ceiling area of any room or space may be Class C material in occupancies where interior finish of Class A or Class B is required.

4. LIMITATIONS

Roppe 700 Series Wall Base is for indoor use only. Do not install on any surface exposed to moisture or extreme temperature changes. Do not install in areas subject to vegetable or petroleum based oils & greases. Fading can

occur from extensive exposure to heavy direct or glass-filtered sunlight, or unfiltered ultra-violet rays.

5. INSTALLATION

General Preparation and Conditioning

Allow all trades to complete work prior to installation of 700 Series Wall Base. Deliver all materials to the installation location in its original packaging with labels intact. Maintain the installation area, material, and adhesive between 65° F (18° C) and 85° F (30° C) for at least 48 hours before installation, during installation, and after the installation.

Wall Surface Inspection

Use only on structurally sound interior wall surfaces such as dry plaster, cured drywall, exterior grade plywood (Group 1, CC type), concrete and masonry that is clean, smooth, dry and structurally sound. All surfaces must be free from moisture, alkali, old adhesive, dust dirt, wax, oil, grease, loose paint or plaster, nonporous wall coverings or paints and other extraneous coatings or materials that could prevent a successful bond. Any rough or uneven surfaces may telegraph through the wall base. Follow the manufacturer's recommendations for any patching materials.

Adhesive for Porous Substrates

1100 Wall Base Adhesive is a premium solvent free Acrylic adhesive with aggressive wet suction grip for all Roppe Wall Base products. Coverages are described on the 1100 Wall Base Adhesive quick spec.

Adhesive for Non-Porous Substrates

Use a premium contact adhesive for installation over all non-porous substrates such as metal, FRP panels, etc.

6. MAINTENANCE

Do not clean, rub or apply lateral or vertical pressure to the 700 Series Wall Base for at least 72 hours after the installation is complete to allow the adhesive to properly cure. 700 Series Wall Base can be routinely cleaned by wiping with a soft cloth slightly dampened with warm water or by using a properly diluted neutral pH cleaner. Some disinfectants, cleaning agents, floor maintenance products and pesticides may stain or damage the surface of the 700 Series Wall Base. If applying finish to flooring, take necessary precautions to keep finish from the 700 Series Wall Base. If applying finish to the 700 Series Wall Base, test inconspicuous area first for compatibility.

7. AVAILABILITY AND COST

Products are available through Roppe distributors. Contact Roppe Customer Service (800) 537-9527 or visit www.roppe.com.

8. TECHNICAL ASSISTANCE

Technical service information and assistance may be obtained by calling Roppe Customer Service at 1-800-537-9527, or by visiting www.roppe.com.

700 Series Wall Base

MADE IN THE USA

PRODUCT QUICK SPEC



ROPPE.

Proven. Flooring. Experiences.



9. SAMPLES

Obtain samples by calling Roppe Customer Service at 1-800-537-9527, or by visiting www.roppe.com.

10. LIMITED WARRANTY

Limited two (2) Year Manufacturer's Warranty

For complete substrate preparation, installation and/or maintenance instructions please visit www.roppe.com

