



Available Color: Black



The Deep-Freeze Mat™ is the only rubber mat specifically formulated to perform in deep-freeze environments. Tested to withstand temperatures to -40° Fahrenheit, this anti-slip matting features a raised knob solid top surface to enhance traction, and is designed for use in meat lockers, walk-ins, and other specialty freezer applications.

| Test                      | Test Description                      | *Results   |
|---------------------------|---------------------------------------|--|
| ASTM D-395                | Compression Set                       | @ 25%: 2.2%  |
| ASTM D-575                | Compression Deflection                | @ 25%: 21.1 lbs/in <sup>2</sup><br>@ 50%: 75.1 lbs/in <sup>2</sup>   |
| ASTM D-1171               | Ozone                                 | No Cracking  |
| ASTM D-3884-01            | Abrasion Resistance (weight loss)     | @1,000 cycles: 0.78 grams (1.22%)  |
| ASTM D-1053-92a(01)e1     | Low Temperature Torsional Stiffness   | T <sub>2</sub> : -25.0°<br>T <sub>5</sub> : -40.5°<br>T <sub>10</sub> : -45.0°<br>T <sub>100</sub> : -49.5°  |
| ASTM D-2859/CPSC FF-170   | Surface Flammability/Carpets and Rugs | Pass   |
| ASTM D-2137-94 (Method A) | Low Temperature Brittleness           | -37°C  |
| ASTM D-1329-02            | Low Temperature Retraction            | TR <sub>10</sub> : -45°C<br>TR <sub>30</sub> : -39°C<br>TR <sub>50</sub> : -33°C<br>TR <sub>70</sub> : -23°C |

\*All testing of NoTrax® floor matting has been performed by an independent testing laboratory.

06/2014



Food Service



Anti-Slip



Protection



Custom



Cold Resistant

- Raised knob solid surface enhances traction
- Tested to withstand temperatures to -40° Fahrenheit
- Low profile for easy cart traffic
- Made with MicroStop™ anti-microbial rubber compound
- Thickness: 3/8"
- Stock Sizes: 2' x 5', 2' x 8', 3' x 5', 3' x 8', 4' x 5', 4' x 8'
- Roll Sizes: 2' x 60', 3' x 60', 4' x 60'

**765:**

| QUALITY METER     | FAIR | GOOD | BETTER | BEST | SUPERIOR |
|-------------------|------|------|--------|------|----------|
| grease resistance | NR   |      |        |      |          |
| comfort           |      |      |        |      |          |
| drainage          | N/A  |      |        |      |          |
| wearability       |      |      |        |      |          |
| traction          |      |      |        |      |          |

