



Interior & Exterior Designs Installation Guidelines

ATTENTION: Rolls are shipped FACE OUT, Good must be handle (face out) at all times during installation, failure to follow these instruction will void any and all warranties.

When installing the Infinity Fabrics' flooring products, we recommend the use of I.F. Adhesive and I.F. Seam Sealer. If these are not available, use only an adhesive and seam sealer, which will bond to Vinyl. Specify level of moisture for Indoor or Outdoor use. I.F. products are used in either Indoor or Outdoor applications and are low VOC emitting.

Each of the Infinity Fabrics, 10' width products are shipped with full selvedge and are thus more protected during shipping. The sides of every installation must be cut and those, which are being seamed, must then be sealed. It is not necessary to seal the edges bordering a wall, as these fabrics have an extremely high face-to-backing bond.

When cutting, it is best to cut from the face of the fabric, always using a new and sharp razor blade. Dull blades will often damage the product or produce rough edges.

Follow the Adhesive and Seam Sealer instructions, as to set up times.

A clean cut will allow for reduced seam visibility. However, seams are visible in these types of product installations and should be expected.

Note: "T" Seams are not advisable in most carpet installations and the same is true for each of these products.

When using glue on a large install, (Remembering the carpet cannot be reverse rolled), using 5 gallon buckets or pieces of wood across the width to hold and elevate the carpet away from its self is required, (vinyl products can crease) this method will help eliminate this issue.